



Windows Powered Smart Card Customer Request Sheet

Please fill out this sheet completely. Upon receipt of this sheet, CardLogix shall create two cards that can then be used for prototype purposes. The items in **bold** are the default configuration parameters.

ATR Selection

Select the ATR String to be returned

- Use Standard CardLogix ATR (0x00 0x43 0x4C 0x58 0x2D 0x31 0x30 0x30)**
- Use the following 8 byte ATR: _____

File System Allocation

Specify the number of to reserve on the card for a file system

- Use default: 8kb for file system, 16 bytes per sector**
- Custom: 2-62 kb for file system, 8, 16, 32 bytes per sector

Action Control Lists

Specify how many different action control lists are on the card (used to control access to files on the card)

- Use default: 16 files, 8 concurrently open**
- Custom: 5-64 files, 4-64 concurrently open

Cryptography

Select the desired encryption scheme/schemes. Both DES/Triple DES and RSA/SHA 1 may be specified.

- DES and Triple DES
- RSA and SHA 1
- No Encryption**

Authentication

Specify how files will be protected. Both Password/Pin and DES/Triple DES may be specified.

- Password or PIN
- DES and Triple DES
- NONE**

Visual Basic Runtime Environment

Allow the card to run VB applications

- Yes**
- No