

SmartCard-HSM Data Sheet

Order No	510040001 SmartCard-HSM USB-Token (4.1-P6) 510040101 SmartCard-HSM Mini-SIM (4.1-P6) 510040201 SmartCard-HSM Dual-IF (4.1-P6) 510040401 SmartCard-HSM Micro-SIM (4.1-P6)
Purpose	The SmartCard-HSM is a light-weight hardware security module for secure key generation, storage and use. It has been designed for PKI and cryptographic systems with low to moderate load. The unique build in support for card verifiable certificates as defined in BSI TR-03110 (Extended Access Control) makes a SmartCard-HSM the perfect choice for storing key material in a distributed Public Key Infrastructure. A trusted channel and public key attestation allow remote key generation and certificate issuance. Advanced key management functions provide for key backup and device clustering in key domains.
Authentication	User-PIN / Transport-PIN Public Key Authentication with CV-Certificates Chip Authentication V2.0 based on BSI TR-03110 with Secure Messaging (AES, TDES) Peer authentication in key domains
Key Types	RSA 1024, 1536, 2048, 3072 and 4096 bit ECC 192, 224, 256, 320, 384, 512 and 521 bit on GF(p) AES 128, 192 and 256 bit
Algorithms	Generate key (RSA, ECC, AES) RSA Sign (Raw, PKCS#1 V1.5, PSS, +SHA-1/256/384/512) ECDSA Sign (Raw, SHA-1, SHA-256, SHA-384 and SHA-512) Key Agreement (RSA OAEP (<=3072), ECDH Raw and ECDH Authenticated) AES Key Derivation with Export (CBC, CMAC, NIST SP 800-56C) Wrap / Unwrap Key under AES-256 Key Encryption Key
Random Number	Class DRG.3 as defined in AIS 20
Memory Size	125Kb Flash RSA 4096 key typically 4000 byte ECC 521 key typically 2500 byte AES 256 key typically 250 byte All key sizes plus memory space for meta-data (e.g. certificates)
Performance	RSA 1024: 50 ms ECDSA/ 256: 50 ms RSA 1536: 70 ms ECDH 256: 60ms RSA 2048: 120 ms ECDSA 512: 90 ms RSA 3074: 240 ms ECDH 512: 120 ms RSA 4096: 1060 ms RSAGEN 2048: 10 sec ECGEN 256: 1 sec RSAGEN 4096: 25 sec ECGEN 512: 2 sec
Data Retention Endurance	25 years 500.000 write cycles
Platform Certification	Common Criteria EAL 6+ (NSCIB-CC-180212) No composite applet certification performed